

# IRONER

## TFI 8030

---



### STANDARD FEATURES & BENEFITS

- Ergonomic cylinder heated ironer
- Steam or electric heating
- Extended heat transfer path
- Large surface contact with linen ( 330°)
- Finger protection panel and emergency button for more safety
- Easy to use manual controller
- Indication of ironing temperature and speed
- Frequency controlled motor
- Reverse working possibility to take stucked linen
- Possibility for Integration with folding machines

TOLON

# IRONER

## TFI 8030

| MODEL                              | UNIT              | TFI 8030                              |
|------------------------------------|-------------------|---------------------------------------|
| Roll diameter                      | mm                | 800                                   |
| Working width                      | mm                | 3000                                  |
| Roll speed                         | m/min.            | 4-9                                   |
| Performance                        | kg/h              | 150-180                               |
| <b>HEATING</b>                     |                   |                                       |
| Electric                           |                   |                                       |
| Electric heating power *           | kW                | 36                                    |
| Steam                              |                   |                                       |
| Evaporation                        | l/h               | 62                                    |
| Steam connection Ø                 | DN                | 40 (1 ½")                             |
| Steam condensate Ø                 | DN                | 20 (¾")                               |
| Steam Pressure                     | mbar              | 400-600                               |
| Steam Consumption                  | m <sup>3</sup> /h | 200                                   |
| <b>VOLTAGE/ELECTRIC CONNECTION</b> |                   |                                       |
| Electric                           |                   |                                       |
|                                    | 3ph 50Hz          | 200/208/220/240/380/400/415/440/480 V |
|                                    | 3ph 60Hz          | 200/208/220/240/380/400/415/440/480 V |
| Steam                              |                   |                                       |
|                                    | 1ph 50Hz          | 200/208/220/240 V                     |
|                                    | 1ph 60Hz          | 200/208/220/240 V                     |
| <b>MOTOR</b>                       |                   |                                       |
| Roll motor                         | kW                | 1,5                                   |
| <b>DIMENSIONS (WxDxH)</b>          |                   |                                       |
| Standard                           | mm                | 4200x1630x1350                        |
| Packed                             | mm                | 4250x1730x1450                        |
| <b>WEIGHT</b>                      |                   |                                       |
| Net                                | kg                | 2360                                  |
| Gross                              | kg                | 2460                                  |
| <b>SOUND LEVEL</b>                 |                   |                                       |
|                                    | db(A)             | < 60                                  |

\*Output calculated at 380V/IIIphase.