

TOLON



TBW16 – 70

Technical Specifications

TOLON Barrier Washers

TBW 16-22-27-35-50-70

Drum volume:

158 l – 220 l – 266 l – 347 l – 489 l – 694 l

Dry Load:

16 kg – 22 kg – 27 kg – 35 kg – 49 kg – 70 kg

Heating:

Electric, Steam or Dual

Control System:

Programmable control, touch screen

Dimensions (WxDxH):

984 x 914 x 1398 mm
1184 x 914 x 1398 mm
1201 x 1098 x 1580 mm
1359 x 1098 x 1580 mm
1654 x 1098 x 1580 mm
2061 x 1098 x 1580 mm

Motor:

2,2 kW – 2,2 kW – 4 kW – 4 kW – 5,5 kW – 7,5 kW

Electric heating power:

12 kW – 18 kW – 18 kW – 27 kW – 36 kW – 45 kW

G-force:

350 – 375 G

Weight:

438 kg – 471 kg – 886 kg – 926 kg – 1063 kg – 1190 kg

TOLON

OPTIONS

- Automatic weighing system
- 2nd drain valve on 1 side 3"
- 3rd water inlet for TBW16 and TBW22 only
- Soap box
- UPS – Drum positioning system: protection kit in case of power failure, only with brake.
- 6 extra dosing signals
- Titration valve for samples
- Stainless steel AISI 304 cabinet
- Maritime wooden box packaging
- Printer
- Low steam pressure
- Plinth for loading height at 850 mm
- Stainless steel sanitary frame
- Special voltages

TOLON

STANDARD FEATURES & BENEFITS

- Barrier washers
- 2 opposed doors for loading and unloading. Door locks with safety opening.
- G-force 350 for TBW 16 and TBW22 and G-force 375 for TBW27, TBW35, TBW50 and TBW70
- Grey skin plate outer casing
- Stainless steel AISI304 drum and tub
- Electric, steam, or dual heating
- CE approval
- Motor brake for automatic drum positioning
- 8 programmable signals for automatic liquid dosing
- 7" touch screen control with 37 languages
- Imbalance inverter for elongating the components' lifetime and reducing washing times
- Standard 2 water inlets
- All barrier washers incorporate the necessary features for WETCLEANING